


High frequency solar inverter PV1800 VPM Series (1KW-5KW)




Features

- Rated power: 1-5KW
- Pure sine wave output
- Smart LCD setting (Working modes, Charge Current, Charge Voltage, etc).
- Built in MPPT 60A/80A solar charge controller
- Combining solar system, AC utility, and battery power source to supply continuous power
- Overload, short circuit and Deep discharge protection
- Cold start function
- Support USB, RS485 monitoring function
- WIFI remote monitoring (optional)
- Compatible to generator
- Support parallel operation up to 3 units (available for 3KW-5KW 48V)


Introduction

This is a multi-function inverter/charger, combining functions of inverter, MPPT 60A/80A solar charger and battery charger to offer uninterruptible power support with portable size. Its comprehensive LCD display offers user-configurable and easy-accessible button operation such as battery charging current, AC/solar charger priority, and acceptable input voltage based on different applications.


Back panel printing description



1. LCD Display
2. Status Indicator
3. Charging Indicator
4. Fault Indicator
5. Function Buttons




6. AC input
7. AC output
8. Circuit breaker
9. Battery input
10. PV input
11. Power on/off switch
12. RS-485 Communication port
13. USB
14. Dry contact
15. USB wifi



[PV1800 VPM 2-3K]

Solar system connection



Specification

| MODEL | PV18-1012 VPM | PV18-2024 VPM | PV18-3024 VPM | PV18-3048 VPM | PV18-4048 VPM | PV18-5048 VPM | |
|--------------------------------|---------------------------------------|--|----------------|----------------|----------------|----------------|--|
| Default Battery System Voltage | | 12VDC | 24VDC | 48VDC | | | |
| INVERTER OUTPUT | Rated Power | 1000VA / 1000W | 2000VA / 2000W | 3000VA / 3000W | 3000VA / 3000W | 4000VA / 4000W | |
| | Surge Power | 2000VA | 4000VA | 6000VA | 6000VA | 8000VA | |
| | Waveform | Pure sine wave | | | | | |
| | AC Voltage Regulation (Batt,Mode) | 220VAC~240VAC(Setting) | | | | | |
| | Inverter Efficiency(Peak) | 90%~93% | | | | | |
| Transfer Time | 10ms(UPS / VDE4105) / 20ms(APL) | | | | | | |
| AC INPUT | Voltage | 230VAC | | | | | |
| | Selectable Voltage Range | 170~280VAC(UPS) / 90~280VAC(APL) / 184~253VAC(VDE) | | | | | |
| | Frequency Range | 50Hz / 60Hz (Auto sensing) | | | | | |
| BATTERY | Normal voltage | 12VDC | 24VDC | 48VDC | | | |
| | Floating Charge Voltage | 13.7VDC | 27.4VDC | 54.8VDC | | | |
| | Overcharge Protection | 15VDC | 30VDC | 60VDC | | | |
| SOLAR CHARGER & AC CHARGER* | Maximum PV Array Open Circuit Voltage | 105VDC | 145VDC | 145VDC | | | |
| | PV Array MPPT Voltage Range | 15~105VDC | 30~120VDC | 60~130VDC | | | |
| | Standby Power Consumption | 2W | | | | | |
| | Maximum PV Array Power | 720W | 1500W | 4000W | | | |
| | Maximum Solar Charge Current | 60A | | | 80A | | |
| | Maximum Efficiency | 98% | | | | | |
| | Maximum AC Charge Current | 10A or 20A | 20A or 30A | 60A | | | |
| Maximum Charge Current | 70A | 80A | 140A | | | | |
| MECHANICAL SPECIFICATIONS | Machine Dimensions (W*H*D)(mm) | 224*337*98 | 290*342*125 | 297.5*468*125 | | | |
| | Package Dimensions (W*H*D)(mm) | 299*392*184 | 408*412*240 | 638*395*241 | | | |
| | Net Weight(kg) | 5 | 7.4 | 12 | | | |
| | Gross Weight(kg) | 5.5 | 9.5 | 13.5 | | | |
| OTHER | Humidity | 5% to 95% Relative Humidity (Non-condensing) | | | | | |
| | Operating Temperature | 0°C~50°C | | | | | |
| | Storage Temperature | -15°C ~60°C | | | | | |